

Technical Data Sheet

Passive Roof

The Passive Roof system is an engineered solution providing **superior thermal protection**.

It features significant external, over-rafter insulation to create a continuous thermal layer, minimizing thermal bridging. The insulation thickness is specified according to regional climatic demands.

The primary technical advantage is an optimized thermal envelope that reduces heat gain in summer and heat loss in winter, leading to significant energy savings.

This system is engineered for robust performance in climates with harsh winters or very hot summers, ensuring year-round comfort and efficiency.

Roof Assembly Composition




PASSIVE PRESET / Thickness: 461mm

- | | |
|---|-----------|
| 1. Battens | 25x95 mm |
| 2. Counter Battens | 45x45 mm |
| 3. Wind-Moisture / Diffusion Membrane | 0.2 mm |
| 4. Primary Insulation / Soft Mineral Wool | 400 mm |
| 5. Rafters | 45x390 mm |
| 6. Vapor Barrier / Diffusion Membrane | 0.2 mm |
| 7. Closing Boards And Tie Boards | 45x195mm |
| 8. Purlins | 195x195mm |



CONSTRUCTION SYSTEM / Roof Presets

Thermal Performance Metrics



U-Value: Thermal Transmittance

U-value measures how well a building component (like a wall, roof, or window) prevents heat from passing through it. It indicates the rate of heat transfer through a material or assembly for a given temperature difference. A lower U-value signifies better insulation, meaning less heat loss or gain.

U-Value: 0,102 $W/(m^2K)$



Condensate: 100 kg/m²



Thickness: 55,85 cm
Weight: 84 kg/m²

Temp. amplitude damping (1/TAV): 27,2



Moisture content of wood: + 100,0%



Interior surface 19,3°C (52%)



Phase shift: 9.2h



Contribution to the greenhouse effect:



insufficient

excellent

Drying time: -



insufficient

excellent

Drying reserve: 9067 g/m²a



insufficient

excellent

Heat storage capacity: 43 kJ/m²K



insufficient

excellent

R-Value: Thermal Resistance

R-value measures how well a material resists heat flow. A higher R-value indicates better insulation, meaning the material is more effective at preventing heat from passing through it. This is crucial for building insulation, where it helps to keep homes warmer in the winter and cooler in the summer, reducing energy consumption and costs.

R-Value: 9,522 m^2KW



Condensate: 100 kg/m²



Thickness: 55,85 cm
Weight: 84 kg/m²

Temp. amplitude damping (1/TAV): 27,2



Moisture content of wood: + 100,0%



Interior surface 19,3°C (52%)



Phase shift: 9.2h



Contribution to the greenhouse effect:



insufficient

excellent

Drying time: -



insufficient

excellent

Drying reserve: 9067 g/m²a



insufficient

excellent

Heat storage capacity: 43 kJ/m²K




insufficient

excellent

Hygrothermal Analysis

Relative Humidity & Moisture Control



Drying reserve Drying reserve according

to DIN 4108-

3:2018: **9067 g/(m²a)**

At least required by DIN 68800-2: **100 g/(m²a)**


Mould protection The temperature of

the inside surface is

19,3 °C leading to a relative humidity on the surface of 52 %.


Mould formation is **not expected** under these conditions.

Temperature & Condensation Risk



The following results are properties of the tested component alone and do not make any statement about the heat protection of the entire room.

Surface Temperature Analysis



- phase shift: **9,2 h**
- Heat storage capacity (whole component): **57 kJ/m²K**
- Amplitude attenuation: **27,2**
- Thermal capacity of inner layers: **43 kJ/m²K**
- TAD: **0,037**